



European Union Monitoring Mission in Georgia

**64a I. Chavchavadze Avenue,
0179 Tbilisi, Georgia, Tel: + 995 32 2 721 800**

www.eumm.eu

CORRIGENDUM N° 1

Supply of Observation and Patrolling Equipment & Accessories

Ref: N° EUMM-26-10123

The following document of the Tender dossier shall be modified as follows:

EUMM-26-10123 Technical-specifications, Lot 4: Spare parts & accessories, item no. 4.. Column 2. Specifications required:

Instead of:

Lot 4: Spare parts & accessories				
1. Item Number	2. Specifications Required	3. Specifications Offered	4. Notes, remarks, ref to documentation	5. Evaluation Committee's notes
4.1	<p>Hard case for observation equipment QTY:12 pc</p> <p>Technical Specifications:</p> <ul style="list-style-type: none"> • Exterior dimensions: maximum 559 × 406 × 267 mm • Interior dimensions: <i>minimum 521 × 292 × 203 mm (20.5 × 11.5 × 8 in) or equivalent usable volume.</i> • Weight: maximum 5.5 kg with empty foam/dividers or equivalent lightweight construction. • Lid depth: minimum 44 mm (1.75 in); base depth: <i>minimum 159 mm (6.25 in).</i> • Material: high-impact copolymer polypropylene with polyurethane foam lining or equivalent ultra-light but rugged polymer construction. • Color: black (non-camouflage); other neutral colors acceptable if structurally equivalent. • Closure system: <i>double-throw stainless steel latches with TSA-approved lock holes; minimum two integrated padlock eyelets.</i> • Lid closure: automatic pressure equalization valve (adjustable for altitude changes) and crushproof/slice-resistant lid design. • Handle: retractable trolley handle with wheels • Environmental protection: <ul style="list-style-type: none"> • Watertight O-ring seal (IP67 or equivalent submersion resistance up to 1 m for 30 min). • Dustproof and crushproof construction. • Temperature range: <i>-40°C to +99°C (-40°F to +210°F) operating tolerance or equivalent thermal stability.</i> • Meets or exceeds MIL-STD-810G for impact, vibration, and environmental testing or equivalent certified ruggedness. <p>Warranty</p> <ul style="list-style-type: none"> • Minimum warranty: 24 months from delivery or manufacturer's standard warranty, whichever is longer. 			

Instead of:

Lot 4: Spare parts & accessories				
1. Item Number	2. Specifications Required	3. Specifications Offered	4. Notes, remarks, ref to documentation	5. Evaluation Committee's notes
	<p>Reference model: Peli 1535 Air Case with Divider Set - Black or structurally equivalent professional carry-on hard case with padded dividers.</p> <p>Divider set (included per case)</p> <ul style="list-style-type: none">Fully customizable padded divider system:<ul style="list-style-type: none">Padded dividers with Velcro®-compatible hook-and-loop material for modular internal organization.Includes minimum 4 long dividers and 5 short dividers (or equivalent configurable layout for optics, electronics, and accessories).High-density foam padding for equipment protection; configurable for sensitive observation/monitoring gear.			

Shall be replaced by:

Lot 4: Spare parts & accessories				
1. Item Number	2. Specifications Required	3. Specificati ons Offered	4. Notes, remarks, ref to documentation	5. Evaluation Committe e's notes
4.1	<p>Hard case for observation equipment QTY:12 pc</p> <p>Technical Specifications:</p> <ul style="list-style-type: none"> • Exterior dimensions: maximum 559 × 406 × 267 mm • Interior dimensions: <i>518 × 284 × 183 mm or equivalent usable volume .</i> • Weight: maximum 5.5 kg with empty foam/dividers or equivalent lightweight construction. • Lid depth: minimum 44 mm (1.75 in); base depth: <i>minimum 132 mm.</i> • Material: high-impact copolymer polypropylene with polyurethane foam lining or equivalent ultra-light but rugged polymer construction. • Color: black (non-camouflage); other neutral colors acceptable if structurally equivalent. • Closure system <i>Press and Pull heavy duty plastic latches for secure closure or equivalent .</i> • Lid closure: automatic pressure equalization valve (adjustable for altitude changes) and crushproof/slice-resistant lid design. • Handle: retractable trolley handle with wheels • Environmental protection: <ul style="list-style-type: none"> • Watertight O-ring seal (IP67 or equivalent submersion resistance up to 1 m for 30 min). • Dustproof and crushproof construction. • Temperature range: <i>-17.8°C to +60°C</i> operating tolerance or equivalent thermal stability. • Meets or exceeds MIL-STD-810G for impact, vibration, and environmental testing or equivalent certified ruggedness. <p>Warranty</p> <ul style="list-style-type: none"> • Minimum warranty: 24 months from delivery or manufacturer's standard warranty, whichever is longer. 			

Shall be replaced by:

Lot 4: Spare parts & accessories				
1. Item Number	2. Specifications Required	3. Specificati ons Offered	4. Notes, remarks, ref to documentation	5. Evaluation Committe e's notes
	<p>Reference model: Peli 1535 Air Case with Divider Set - Black or structurally equivalent professional carry-on hard case with padded dividers.</p> <p>Divider set (included per case)</p> <ul style="list-style-type: none">• Fully customizable padded divider system:<ul style="list-style-type: none">• Padded dividers with Velcro®-compatible hook-and-loop material for modular internal organization.• Includes minimum 4 long dividers and 5 short dividers (or equivalent configurable layout for optics, electronics, and accessories).• High-density foam padding for equipment protection; configurable for sensitive observation/monitoring gear.			

All other terms and conditions of the subject Tender Dossier remain unchanged.

All information contained in this corrigendum and attachment shall now be considered an integral part of the Tender Dossier, ref: EUMM-26-10123.